



**ALL OF OUR EFFECTS ARE INSPIRED BY MOTHER NATURE.
ALL OF OUR MACHINES ARE DESIGNED TO RESPECT HER.**

COMPANY PROFILE

Established in 1984, Antari has been at the forefront of innovation as a leading fog machine manufacturer. Beginning with a focus on stage fog machines, Antari quickly became synonymous with cutting-edge technology and quality in the entertainment industry.

Over the years, Antari has diversified its expertise, expanding the application of its fog machine technology to areas beyond the stage. The company's commitment to excellence led to the incorporation of its technology in security and fire training. Antari's fog machines have proven instrumental in creating realistic training environments, enhancing preparedness and safety measures.

With a rich history spanning several decades, Antari has consistently demonstrated a dedication to pushing the boundaries of what fog machine technology can achieve. The company's products are renowned for their reliability, performance, and versatility, making Antari a trusted name in both the entertainment and safety sectors.

As a pioneer in fog machine manufacturing, Antari continues to be a driving force in the industry, providing innovative solutions that meet the evolving needs of its diverse clientele. Antari's legacy is built on a foundation of passion for technology, a commitment to quality, and a vision for enhancing experiences across various domains.

CONTENTS

NEW PRODUCT

FAZE MACHINE 01

F-8 02

UNIVERSAL VOLTAGE FAZE MACHINE 03

F-12 04

STAGE / ENTERTAINMENT

UNIVERSAL VOLTAGE FOG MACHINE 05

M-12 06

FOG MACHINE 08

Z-3000III 08

Z-1500III 09

Z-1200III 10

Z-1000III 11

Z-800III / W-508 12

M-8 14

M-10 15

M-5 16

IP-RATED FOG MACHINE 17

IP-3000 17

IP-1600 18

FAZE MACHINE 20

F-7X 20

F-6 21

F-1 22

Z-390 23

Z-350 24

HAZE MACHINE 26

HZ-1000 26

HZ-500 27

HZ-400 28

HZ-350 29

HZ-100 30

JET FOG MACHINE 31

M-9 32

M-7X 33

Z-1520 34

PORTABLE FOG MACHINE 35

MB-20X 35

MB-1 36

UNIVERSAL VOLTAGE CO2 FOG MACHINE 37

CH-1 38

LOW FOG MACHINE 39

DNG-250 40

DNG-100 41

ICE-101 42

SNOW MACHINE 43

S-600 44

S-500 45

S-200X 46

S-100X 47

SW-300 48

SW-250 49

BUBBLE MACHINE 50

B-200 51

B-100 / W-101 52

EFFECT FAN 53

AF-6 54

AF-5X 55

AF-4 56

AF-3 57

FIRE TRAINING

FOG GENERATOR 58

FT-200 59

FT-100 60

FT-70 61

FT-20X 62

SCENT

SCENT MACHINE 63

ARO SCENT 63

SCN-600 64

UV EFFECTS

DARKFX STRIP SERIES 66

STRIP 1020 66

STRIP 510 67

STRIP 510 IP 68

DARKFX WASH SERIES 69

WASH 2000 IP 69

WASH 2000 70

DARKFX SPOT 71

SPOT 1750 71

SPOT 670 72

SPOT 510 IP 73

DARKFX DRIVE 74

DRIVE 4 MKII 74

ACCESSORIES

LIQUID SUPPLY 76

LCU-2S / LCU-1S

CONTROL MODULE 77~78

WTR-110 , TIMO-WTR-90 , TIMO-WTR-70_80 ,

TIMO-WTR-40_50_60 , WTR-20 , WTR-10

REMOTE 79~81

M-20 , M-21 , M-30PRO , M-31

Z-3 , Z-8 , Z-10 , Z-40 ,

Z-50 , BCR-1 , BCT-1 , HC-1

HCR-1 , MCR-1F , MCT-2 , SC-2

SC-3 , SC-4

HANGING BRACKET SET 81

M-9-HB , M-5-HB , SW-300-FB

FLUID TUBES / FILTERS 81

FT-4 , FT-6

FLF-4 , FLF-6

FTA-64 , FTA-66 , FTA-664

REMOTE CONTROL EXTENSION CABLES 81

EXT-1

EXT-3 , EXT-4 , EXT-6

EXT-5

ADAPTORS 82

FTA-1 , FTA-2A , FTA-200 , FTA-11, FT-10

FLIGHT CASE 82

FCH-1 , FDNG-250 , FZ-350 , FX-4 , FX-6

FLUID 83~88

FOG FLUID 84

FLG , FLH , FLJ , FLR , FLY , FLZ

FLL , FLC , FLM-05S , FLM-05P

HAZE FOG FLUID 85

HZL , HZL-W , CHL-2

BUBBLE FLUID 85

BL

SNOW FLUID 87

SL-UV , SL-C , SL-H , SL-AN , SL-N , SL-A , SL

OTHERS 88

MG-550 , C-300 , UVL-01

SCENT 88

P-9 , P-7 , P-6 , P-4 , P-2 , P-1

FIRE TRAINING SMOKE FLUID 86

FLM-05P

FLP

ACCESSORIES LIST 89~92

SPEC CHART 93~94

S T A G E / E N T E R T A I N M E N T

**ANTARI F-8 TYPHON: THE ULTIMATE STADIUM FAZER
UNMATCHED POWER, UNRIVALED PERFORMANCE.**

The Antari F-8 Typhon delivers monumental output, designed specifically for stadiums and arenas. Its precision design fills massive spaces effortlessly. With unparalleled performance and precision airflow, nothing on the market compares. Built for reliability and impact, the F-8 Typhon's power, durability, and performance sets the standard for large-scale effects.















STAGE / ENTERTAINMENT ESSENTIAL ELEGANCE, REALISTIC BRILLIANCE

F-12 Nebula, the world's first universal voltage fazer from Antari, engineered for professionals who need reliable, consistent fog output—anywhere in the world. Its advanced heater design using low temperature to produces dry and odorless fog, making it ideal for theaters and indoor venues. It is designed to perform flawlessly even in environments with unstable voltage, ensuring smooth and uninterrupted operation. Created with professional settings in mind, this innovative fazer raises the bar for versatility and performance.



NEBULA F-12 Universal Voltage Faze Machine

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
 MANUAL  TIMER  3 PIN  5PIN	 WIRELESS  W-DMX	> N/A
RATED VOLTAGE	RATED POWER	
> AC 100 - 240V, 50 / 60 Hz	> 100V 6.0A 500W > 120V 6.5A 750W > 240V 5.5A 1,300W	
FLUID CONSUMPTION	COMPATIBLE FLUID	
> 9 ml/min (100% Output)	 > FLG-5E > FLH-5E	
DIMENSION	WEIGHT	
 L 399 mm L 15.70 inch W 444 mm W 17.48 inch H 268 mm H 10.56 inch	 14.6 kg 32.18 lbs	
	 Neutrik powerCON TRUE 1 Connector Power	



S T A G E / E N T E R T A I N M E N T

ONE MACHINE, INFINITE ATMOSPHERES

UNIVERSAL VOLTAGE, GLOBALLY UNLEASHED!

Antari introduces the revolutionary Universal Voltage High Power Fog Machine, setting a new standard in atmospheric effects. This cutting-edge device combines unparalleled performance with adaptability, boasting the first-ever universal voltage compatibility. From 100V to 240V, the machine seamlessly integrates into any global power grid, making it an ideal choice for events worldwide. Delivering an impressive output of dense, lingering fog, this innovation transforms any environment into a captivating spectacle. Its high-power capabilities ensure extensive coverage, creating an immersive atmosphere for concerts, events, and productions. Antari's commitment to excellence shines through in this fog machine, offering a dynamic blend of versatility, power, and reliability.



M-12 Universal Voltage Fog Machine

CONTROL METHODS		OPTIONAL		INCLUDED ACCESSORIES	
MANUAL	TIMER	3 PIN	5PIN	WIRELESS	W-DMX
RATED VOLTAGE		RATED POWER			
› AC 100 - 240V, 50 / 60 Hz		› 120V 17.0A 2,000W		› 240V 8.5A 2,000W	
FLUID CONSUMPTION		COMPATIBLE FLUID			
› 400 ml/min (100% Output)				› FLG › FLR › FLH › FLY › FLJ › FLZ	
DIMENSION		WEIGHT			
	L 646 mm L 25.43 inch	› 27.2 kg		Neutrik powerCON TRUE 1 Connector Power	
	W 280 mm W 11.02 inch	› 59.97 lbs			
	H 283 mm H 11.14 inch				



STAGE / ENTERTAINMENT FOG MACHINE

Antari Fog Machine – your gateway to the pinnacle of atmospheric innovation.

Dive into a world of possibilities with our cutting-edge Fog Machine collection, featuring the versatile Antari Fog Machine, Fazer Machine, Hazer Machine, and the enchanting Low Fog Machine. This curated pages showcases the epitome of ambiance creation, offering a spectrum of choices to suit every setting. From the mysterious vapor of the fogger to the fine mist of the Fazer to the ethereal allure of the Hazer and the ground-hugging magic of the Low Fog Machine, each product is designed for unmatched atmospheric excellence.

Elevate your events with Antari – where innovation meets enchantment.



Z-3000III

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
------------------------	-----------------	-----------------------------

				
MANUAL	TIMER	3 PIN / 5PIN	WIRELESS	> N/A


RATED VOLTAGE	RATED POWER
----------------------	--------------------

> EU Model : AC 220-240V, 50/60Hz, 10.5A	> 2,500W
--	----------

FLUID CONSUMPTION	COMPATIBLE FLUID
--------------------------	-------------------------

> 250 ml/min (100% Output)	 <ul style="list-style-type: none"> > FLG > FLH > FLJ > FLR > FLY > FLZ
----------------------------	--

DIMENSION	WEIGHT
------------------	---------------

	L 712 mm	L 28.03 inch
	W 275 mm	W 10.82 inch
	H 278 mm	H 10.94 inch
	19.1 kg	42.10 lbs





Z-1500III

CONTROL METHODS



MANUAL TIMER 3 PIN / 5 PIN

OPTIONAL



WIRELESS

INCLUDED ACCESSORIES

> N/A

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 12.5A
> EU Model : AC 220-240V, 50/60Hz, 6.5A

RATED POWER

> 1,500W

FLUID CONSUMPTION

> 150 ml/min (100% Output)

COMPATIBLE FLUID



> FLG > FLR
> FLH > FLY
> FLJ > FLZ

DIMENSION



L 674 mm L 26.54 inch
W 235 mm W 9.25 inch
H 278 mm H 10.94 inch

WEIGHT



13.3 kg
29.32 lbs



Neutrik powerCON TRUE1
Connector Power

Z-1200III

CONTROL METHODS



MANUAL TIMER 5 PIN

OPTIONAL



WIRELESS



CABLE
REMOTE

INCLUDED ACCESSORIES

> Hanging Bracket

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 10.0A
> EU Model : AC 220-240V, 50/60Hz, 5.0A

RATED POWER

> 1,200W

FLUID CONSUMPTION

> 85 ml/min (100% Output)

COMPATIBLE FLUID



> FLG > FLR
> FLH > FLY
> FLJ > FLZ

DIMENSION



L 458 mm L 18.03 inch
W 320 mm W 12.60 inch
H 326 mm H 12.84 inch

WEIGHT



11.0 kg
24.25 lbs



IEC Connector Power



Z-800III

W-508



Z-1000III

CONTROL METHODS

- MANUAL
- 3 PIN
- CABLE REMOTE

OPTIONAL

- TIMER
- WIRELESS

INCLUDED ACCESSORIES

- > Z-10 Cable Remote
- > Hanging Bracket

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 8.5A
- > EU Model : AC 220-240V, 50/60Hz, 4.5A

RATED POWER

- > 1,000W

FLUID CONSUMPTION

- > 60 ml/min (100% Output)

COMPATIBLE FLUID

- > FLG
- > FLR
- > FLH

DIMENSION

L	433 mm	L	17.05 inch
W	281 mm	W	11.06 inch
H	266 mm	H	10.48 inch

WEIGHT

- 7.9 kg
- 17.41 lbs

IEC Connector Power

Z-800III / W-508

Z-800III CONTROL METHODS

- MANUAL
- CABLE REMOTE
- TIMER OPTIONAL
- WIRELESS OPTIONAL

W-508 CONTROL METHODS

- MANUAL
- WIRELESS

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 7.0A
- > EU Model : AC 220-240V, 50/60Hz, 3.5A

INCLUDED ACCESSORIES

- > Z-800III : Z-10 Cable Remote
- > W-508 : W-1 Wireless Transmitter

RATED POWER

- > 800W

FLUID CONSUMPTION

- > 13 ml/min (100% Output)

COMPATIBLE FLUID

- > FLG
- > FLR
- > FLH

DIMENSION

L	315 mm	L	12.40 inch
W	128 mm	W	5.04 inch
H	218 mm	H	8.58 inch

WEIGHT

Z-800III	W-508
4.2 kg	3.8 kg
9.26 lbs	8.38 lbs



STAGE / ENTERTAINMENT MADE TO LAST!

M Series : Unleash the Unyielding Power. Built for the demands of concerts, movie productions, and touring, the M Series is your only choice for heavy-duty performance. Crafted with unparalleled sturdiness and durability, it triumphs in the face of adversity. Engineered to endure the harshest environments, this series thrives where others falter. Choose with confidence as the M Series stands strong, and for seamless mobility and added protection, consider the flight case option—an extra layer of assurance for moving and safeguarding this industrial powerhouse.



M-8

CONTROL METHODS



MANUAL TIMER 3 PIN / 5 PIN WIRELESS

OPTIONAL

INCLUDED ACCESSORIES

> M-21 Control Unit

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 15.0A
- > EU Model : AC 220-240V, 50/60Hz, 7.5A

RATED POWER

> 1,700W


FLUID CONSUMPTION

> 240 ml/min (100% Output)


COMPATIBLE FLUID

- > FLG
- > FLH
- > FLR

DIMENSION

	L	668 mm	L	26.30 inch
	W	320 mm	W	12.60 inch
	H	276 mm	H	10.87 inch

WEIGHT

 22.0 kg
48.5 lbs





M-10

CONTROL METHODS



MANUAL TIMER 3 PIN / 5 PIN WIRELESS

OPTIONAL

INCLUDED ACCESSORIES

> M-20 Control Unit

RATED VOLTAGE

> EU Model : AC 220-240V, 50/60Hz, 12.5A

RATED POWER

> 3,000W

FLUID CONSUMPTION

> 250 ml/min (100% Output)

COMPATIBLE FLUID



> FLG
> FLH
> FLR

DIMENSION



L 697 mm L 27.44 inch
W 319 mm W 12.56 inch
H 300 mm H 11.82 inch

WEIGHT



25.8 kg
56.88 lbs



Neutrik powerCON
Connector Power

M-5

CONTROL METHODS



MANUAL TIMER 3PIN/5PIN WIRELESS

OPTIONAL

INCLUDED ACCESSORIES

> M-20 Control Unit

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 12.5A
> EU Model : AC 220-240V, 50/60Hz, 6.5A

RATED POWER

> 1,500W

FLUID CONSUMPTION

> 160 ml/min (100% Output)

COMPATIBLE FLUID



> FLG
> FLH
> FLR

DIMENSION



L 668 mm L 26.30 inch
W 320 mm W 12.60 inch
H 276 mm H 10.87 inch

WEIGHT



15.5 kg
34.17 lbs



Neutrik powerCON
Connector Power



IP-3000



CONTROL METHODS



MANUAL TIMER 5 PIN WIRELESS

OPTIONAL

N/A

INCLUDED ACCESSORIES

- > W-2 Wireless Transmitter
- > Hanging Bracket

RATED VOLTAGE

> EU Model : AC 220-240V, 50/60Hz, 10.5A

RATED POWER

> 2,500W

FLUID CONSUMPTION

> 250 ml/min (100% Output)

COMPATIBLE FLUID

- > FLG > FLR
- > FLH > FLY
- > FLJ > FLZ

DIMENSION

	L	511 mm	L	20.12 inch
	W	314 mm	W	12.37 inch
	H	394 mm	H	15.52 inch

WEIGHT

	18.6 kg
	41.0 lbs



Neutrik powerCON TRUE 1
Connector Power

IP-1600



CONTROL METHODS



MANUAL TIMER 5 PIN WIRELESS

OPTIONAL

N/A

INCLUDED ACCESSORIES

- > W-2 Wireless Transmitter
- > Hanging Bracket

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 12.5A
> EU Model : AC 220-240V, 50/60Hz, 6.5A

RATED POWER

> 1,500W

FLUID CONSUMPTION

> 150 ml/min (100% Output)

COMPATIBLE FLUID

- > FLG > FLR
- > FLH > FLY
- > FLJ > FLZ

DIMENSION

	L	478 mm	L	18.82 inch
	W	277 mm	W	10.90 inch
	H	358 mm	H	14.10 inch

WEIGHT

	12.6 kg
	27.78 lbs



Neutrik powerCON TRUE 1
Connector Power



STAGE / ENTERTAINMENT FAZE MACHINE

The Antari F Series introduces the revolutionary concept of "Fazer," a term coined by Antari that redefines atmospheric effects. Positioned between traditional foggers and hazers, Fazers bridge the gap with unparalleled innovation. These machines boast zero warm-up time, ensuring instant immersion in captivating atmospheres. What sets them apart is their exceptional ability to make light beams vividly visible, enhancing the impact of lighting and laser displays. The F Series encompasses a versatile range of models, catering to various needs, from portable units for small venues to high-capacity powerhouses for large-scale productions. With Antari's F Series, you enter a realm of limitless creativity, elevating any event or performance into an unforgettable sensory experience. Welcome to the future of atmospheric effects.



F-7X

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
 MANUAL TIMER 3 PIN / 5 PIN	 WIRELESS W-DMX	> N/A
RATED VOLTAGE	RATED POWER	
> US Model : AC 100-120V, 50/60Hz, 13.5A > EU Model : AC 220-240V, 50/60Hz, 8.0A	> 100V 1,400W > 120V 1,600W > 240V 1,900W	
FLUID CONSUMPTION	COMPATIBLE FLUID	
> Fog Mode : 150 ml/min (100% Output) > Faze Mode : 28 ml/min (100% Output)	> FLG-5E > FLH-5E > FLZ-5E	
DIMENSION	WEIGHT	
L 728 mm L 28.66 inch W 428 mm W 16.85 inch H 719 mm H 28.31 inch	53.0 kg 116.85 lbs	Neutrik powerCON TRUE 1 Connector Power



F-6

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
 MANUAL TIMER 5 PIN	 WIRELESS W-DMX	> N/A
RATED VOLTAGE	RATED POWER	
> US Model : AC 100-120V, 50/60Hz, 12.5A > EU Model : AC 220-240V, 50/60Hz, 6.5A	> 1,450W	
FLUID CONSUMPTION	COMPATIBLE FLUID	
> 12 ml/min (100% Output)	> FLG-5E	
DIMENSION	WEIGHT	
L 493 mm L 19.40 inch W 424 mm W 16.96 inch H 280 mm H 11.02 inch	17.2 kg 37.92 lbs	Neutrik powerCON TRUE 1 Connector Power

F-1

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
 MANUAL TIMER 3 PIN / 5 PIN	 WIRELESS W-DMX	> N/A
RATED VOLTAGE	RATED POWER	
> US Model : AC 100-120V, 50/60Hz, 7.0A > EU Model : AC 220-240V, 50/60Hz, 3.5A	> 800W	
FLUID CONSUMPTION	COMPATIBLE FLUID	
> 8.5 ml/min (100% Output)	> FLG > FLY <i>» FLH : Machines manufactured after May 2020 please set to FLG</i> > FLH > FLZ <i>» FLZ & FLY : Applicable to machines manufactured after May 2020</i> > FLR	
DIMENSION	WEIGHT	
L 618 mm L 24.33 inch W 275 mm W 10.83 inch H 382 mm H 15.04 inch	14.1 kg 31.09 lbs	Neutrik powerCON Connector Power



Z-390

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 8.5A
- > EU Model : AC 220-240V, 50/60Hz, 6.5A

FLUID CONSUMPTION

- > 8 ml/min (100% Output)

DIMENSION

L	368 mm	L	14.49 inch
W	340 mm	W	13.39 inch
H	344 mm	H	13.55 inch

OPTIONAL



INCLUDED ACCESSORIES

- > Hanging Bracket

RATED POWER

- > 120V 1,000W
- > 240V 1,450W

COMPATIBLE FLUID



WEIGHT

9.7 kg
21.38 lbs



IEC Connector Power

Z-350

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 6.0A
- > EU Model : AC 220-240V, 50/60Hz, 3.5A

FLUID CONSUMPTION

- > 3 ml/min (100% Output)

DIMENSION

L	320 mm	L	12.60 inch
W	153 mm	W	6.02 inch
H	391 mm	H	15.39 inch

OPTIONAL



INCLUDED ACCESSORIES

- > N/A

RATED POWER

- > 120V 700W
- > 240V 750W

COMPATIBLE FLUID



WEIGHT

8.5 kg
18.74 lbs



IEC Connector Power












STAGE / ENTERTAINMENT

HAZE MACHINE

The Antari HZ Series Haze Machine stands as an essential component for creating mesmerizing atmospheric effects in any lighting and laser beam spectacle. Engineered to perfection, this cutting-edge haze machine effortlessly transforms ordinary environments into extraordinary visual spectacles. Its precision-engineered output ensures that laser beams and lighting effects are brilliantly accentuated, enhancing their visibility and impact. The Antari HZ Series boasts an unrivaled level of reliability and performance, making it the top choice for professional lighting designers and event organizers. Elevate your events to new heights with the Antari HZ Series Haze Machine, where the fusion of light and haze creates an unparalleled sensory experience that will leave a lasting impression.



HZ-1000

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
   		> N/A
MANUAL TIMER 3 PIN / 5 PIN W-DMX		
RATED VOLTAGE	RATED POWER	
> US Model : AC 100-120V, 50/60Hz, 10.0A > EU Model : AC 220-240V, 50/60Hz, 5.0A	> 1,150W	
FLUID CONSUMPTION	COMPATIBLE FLUID	
> 2.2 ml/min (100% Output)	 > HZL > HZL-W	
DIMENSION	WEIGHT	
 L 690 mm L 27.16 inch W 510 mm W 20.07 inch H 610 mm H 24.01 inch	 74.6 kg 164.46 lbs	 Neutrik powerCON TRUE 1 Connector Power



☁️ HZ-500



CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
------------------------	-----------------	-----------------------------

- MANUAL
- TIMER
- 5 PIN

> N/A

> N/A

RATED VOLTAGE	RATED POWER
<ul style="list-style-type: none"> > US Model : AC 100-120V, 50/60Hz, 3.5A > EU Model : AC 220-240V, 50/60Hz, 2.0A 	<ul style="list-style-type: none"> > 120V 400W > 240V 480W

FLUID CONSUMPTION	COMPATIBLE FLUID
> 1.1 ml/min (100% Output)	<ul style="list-style-type: none"> > HZL > HZL-W

DIMENSION	WEIGHT	
<ul style="list-style-type: none"> L 515 mm L 20.28 inch W 375 mm W 14.77 inch H 355 mm H 13.98 inch 	<ul style="list-style-type: none"> 31.5 kg 69.45 lbs 	IEC Connector Power

☁️ HZ-400

CONTROL METHODS	OPTIONAL	INCLUDED ACCESSORIES
------------------------	-----------------	-----------------------------

- MANUAL
- TIMER
- 3 PIN

- WIRELESS

> HC-1 Cable Timer Remote

RATED VOLTAGE	RATED POWER
<ul style="list-style-type: none"> > US Model : AC 100-120V, 50/60Hz, 4.0A > EU Model : AC 220-240V, 50/60Hz, 2.0A 	> 470W

FLUID CONSUMPTION	COMPATIBLE FLUID
> 1.1 ml/min (100% Output)	<ul style="list-style-type: none"> > HZL > HZL-W

DIMENSION	WEIGHT	
<ul style="list-style-type: none"> L 510 mm L 20.08 inch W 320 mm W 12.60 inch H 325 mm H 12.80 inch 	<ul style="list-style-type: none"> 18.5 kg 40.79 lbs 	IEC Connector Power




☁️ HZ-350

CONTROL METHODS



MANUAL TIMER 5 PIN WIRELESS

OPTIONAL



CABLE REMOTE

INCLUDED ACCESSORIES

> W-1 Wireless Radio Transmitter

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 3.5A
> EU Model : AC 220-240V, 50/60Hz, 2.0A

RATED POWER

> 390W

FLUID CONSUMPTION

> 0.8 ml/min (100% Output)

COMPATIBLE FLUID



> HZL
> HZL-W

DIMENSION



L 492 mm L 19.37 inch
W 273 mm W 10.75 inch
H 315 mm H 12.4 inch

WEIGHT



14.2 kg
31.31 lbs



IEC Connector Power

☁️ HZ-100

CONTROL METHODS



MANUAL

OPTIONAL



TIMER



WIRELESS

INCLUDED ACCESSORIES

> N/A

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 3.5A
> EU Model : AC 220-240V, 50/60Hz, 2.0A

RATED POWER

> 390W

FLUID CONSUMPTION

> 0.7 ml/min (100% Output)

COMPATIBLE FLUID



> HZL
> HZL-W

DIMENSION



L 490 mm L 19.30 inch
W 250 mm W 9.84 inch
H 294 mm H 11.57 inch

WEIGHT



13.2 kg
29.10 lbs



IEC Connector Power



S T A G E / E N T E R T A I N M E N T

**JET FOG MACHINES REDEFINED
POWER, PRECISION, PERFORMANCE**

Antari jet fog machines deliver unparalleled power and precision for professional applications. Designed to create dynamic vertical or horizontal fog effects, these machines are perfect for live events, concerts, and theatrical productions.

Equipped with cutting-edge technology, it offers rapid heat-up times, massive output, and consistent performance. Its robust construction ensures reliability in demanding environments

It is designed for ease of use, whether for dazzling stage effects or impactful special effects. Antari's jet fog is the ultimate choice.



M-9

CONTROL METHODS		OPTIONAL	INCLUDED ACCESSORIES
MANUAL	TIMER	WIRELESS	W-2 Wireless Transmitter
3 PIN / 5 PIN	5 PIN	MASTER SLAVE	
RATED VOLTAGE		RATED POWER	
<ul style="list-style-type: none"> > US Model : AC 100-120V, 50/60Hz, 15.5A > EU Model : AC 220-240V, 50/60Hz, 8.0A 		<ul style="list-style-type: none"> > 1,820W 	
FLUID CONSUMPTION		COMPATIBLE FLUID	
<ul style="list-style-type: none"> > 400 ml/min (100% Output) 		<ul style="list-style-type: none"> > FLC 	
DIMENSION		WEIGHT	
	<ul style="list-style-type: none"> L 393 mm L 15.47 inch W 321 mm W 12.63 inch H 420 mm H 16.53 inch 		<ul style="list-style-type: none"> 25.0 kg 55.10 lbs
		<p>Neutrik powerCON TRUE 1 Connector Power</p>	



M-7X

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 13.0A
- > EU Model : AC 220-240V, 50/60Hz, 6.5A


FLUID CONSUMPTION

- > 200 ml/min (100% Output)

DIMENSION

	L	346 mm	L	13.62 inch
	W	193 mm	W	7.60 inch
	H	383 mm	H	15.00 inch


OPTIONAL INCLUDED ACCESSORIES



RATED POWER

- > 1,516W

COMPATIBLE FLUID



WEIGHT

	14.0 kg
	30.80 lbs



Z-1520

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 13.0A
- > EU Model : AC 220-240V, 50/60Hz, 6.5A

FLUID CONSUMPTION

- > 150 ml/min (100% Output)

DIMENSION

	L	418 mm	L	16.46 inch
	W	295 mm	W	11.61 inch
	H	210 mm	H	8.27 inch

OPTIONAL INCLUDED ACCESSORIES



RATED POWER


- > 1,516W

COMPATIBLE FLUID



WEIGHT

	10.4 kg
	22.93 lbs





MB-20X

CONTROL METHODS



MANUAL 3 PIN

OPTIONAL



WIRELESS

CABLE REMOTE

INCLUDED ACCESSORIES

- > FLM-05P Fog Fluid 500 ML
- > FFT-20 Flightcase
- > MB-20X-B Battery
- > MB-20X-BCL Charger

RATED VOLTAGE

- > DC 12V (Battery)
- > AC 100-240V, 50/60Hz (Battery Charger)

RATED POWER

- > 600W

FLUID CONSUMPTION

- > 16 ml/min (100% Output)

COMPATIBLE FLUID



- > FLM-05P

DIMENSION



L 293 mm L 11.54 inch
W 108 mm W 4.26 inch
H 239 mm H 9.41 inch

WEIGHT



8.5 kg
18.74 lbs

MB-1

CONTROL METHODS



MANUAL

OPTIONAL



TIMER

WIRELESS



CABLE REMOTE

INCLUDED ACCESSORIES

- > FLM-05S Fog Fluid 500 ML
- > Flightcase
- > BAT-01 Battery
- > MB-1-BCL Charger

RATED VOLTAGE

- > DC 12V (Battery)
- > AC 100-240V, 50/60Hz (Battery Charger)

RATED POWER

- > 75W

FLUID CONSUMPTION

- > 1.1 ml/min (100% Output)

COMPATIBLE FLUID



- > FLM-05S

DIMENSION



L 225 mm L 8.86 inch
W 67 mm W 2.64 inch
H 113 mm H 4.49 inch

WEIGHT



Without Battery: 1.0 kg 2.20 lbs
With Battery: 1.8 kg 3.97 lbs



S T A G E / E N T E R T A I N M E N T

ANTARI CO2 SERIES: HAZE WITH IMPACT ELEVATE ATMOSPHERE, AMPLIFY IMPACT

The Antari CO2 Series revolutionizes haze generation by utilizing CO2 for unparalleled consistency and efficiency. Designed for professional applications, it produces ultra-fine, long-lasting haze ideal for enhancing lighting effects in concerts, theaters, and live events.

Its CO2-driven technology ensures clean, residue-free haze while delivering exceptional coverage for both indoor and outdoor venues.

Durable, efficient, and precise, the Antari CO2 Series redefines haze generation for bold, unforgettable effects, empowering productions to achieve their boldest visual effects.

Built for reliability and performance.



CHL-2 FLUID

CHL-2 is a high quality oil based liquid for CH-1 cinema haze to produce fine and translucent haze.

The haze produced by CH-1 and CHL fluid can set off the stage lighting beautifully and create a wonderful stage design



CH-1 Universal Voltage CO2 Fog Machine

CONTROL METHODS



MANUAL TIMER 3 PIN / 5 PIN W-DMX

OPTIONAL



W-DMX

INCLUDED ACCESSORIES

- > Pressure Gauge
- > Air Hose

RATED VOLTAGE

- > AC 100-240V, 50 / 60 Hz

RATED POWER

- > 120V 6.0A 700W
- > 240V 5.5A 1.250W

FLUID CONSUMPTION

- > 2 ml/min @40psi / 2.76bar (100% Output)

COMPATIBLE FLUID



> CHL-2

DIMENSION

	L 579 mm	L 22.79 inch
	W 164 mm	W 6.46 inch
	H 311 mm	H 12.25 inch

WEIGHT



Neutrik powerCON TURE 1 Connector Power









Note: The machine requires a CO2 Cylinder, please purchase locally.



STAGE / ENTERTAINMENT LOW FOG MACHINE

The Antari DNG Series is your gateway to awe-inspiring low-lying cloud effects. These cutting-edge machines produce a dense, white fog that hugs the floor, creating an ethereal atmosphere that enchants and mystifies. Engineered with precision, the DNG Series is equipped with advanced technology to deliver a crawler effect, mimicking natural ground-hugging fog. Perfect for theaters, stages, and special events, these fog generators offer unparalleled control and versatility. Transform any space into a mystical wonderland with ease. Elevate your productions and immerse your audience in a world of enchantment with the Antari DNG Series, where fog becomes a breathtaking, floor-level spectacle.

DNG-250

CONTROL METHODS     MANUAL TIMER 3 PIN / 5 PIN	OPTIONAL > N/A	INCLUDED ACCESSORIES > CODNG0600 3 Meter Fog Conducting Hose
RATED VOLTAGE > US Model : AC 100-120V, 50/60Hz > EU Model : AC 220-240V, 50/60Hz	START CURRENT > 120V 75.0A > 240V 36.0A	RATED CURRENT > 120V 16.1A > 240V 7.3A
FOG POWER CONSUMPTION > 120V 1.600W 13.5A > 240V 1.600W 7.0A	FLUID CONSUMPTION > 100 ml/min (100% Output)	COMPATIBLE FLUID > FLL 
DIMENSION  L 922 mm L 36.30 inch W 609 mm W 23.98 inch H 890 mm H 35.04 inch	WEIGHT  130.0 kg 286.60 lbs	 Neutrik powerCON Connector Power



DNG-100

ICE-101

CONTROL METHODS



OPTIONAL

> N/A

INCLUDED ACCESSORIES

- > FTA-11 Diverter
- > FT-10 Fog Conducting Hose

RATED VOLTAGE

- > US Model : AC 100-120V, 50 / 60Hz
- > EU Model : AC 220-240V, 50 / 60Hz

START CURRENT

- > 120V 61.0A
- > 240V 21.0A

RATED CURRENT

- > 120V 6.7A
- > 240V 3.2A


RATED POWER

- > 120V 750W
- > 240V 600W

FLUID CONSUMPTION

> N/A

COMPATIBLE FLUID



DIMENSION

	L	784 mm	L	30.86 inch
	W	608 mm	W	23.93 inch
	H	479 mm	H	18.85 inch

WEIGHT

	72.0 kg
	158.73 lbs

CONTROL METHODS



OPTIONAL

> N/A

INCLUDED ACCESSORIES

- > Z-8 Cable Timer Remote

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 9.5A
- > EU Model : AC 220-240V, 50/60Hz, 5.0A

RATED POWER

- > 1,130W

FLUID CONSUMPTION

- > 25 ml/min (100% Output)

COMPATIBLE FLUID



DIMENSION

	L	670 mm	L	26.38 inch
	W	355 mm	W	13.98 inch
	H	506 mm	H	19.93 inch

WEIGHT

	24.4 kg
	53.79 lbs



IEC Connector Power



STAGE / ENTERTAINMENT

SNOW MACHINE

Step into the enchanting world of special effects with the Antari Special Effect Page, a mesmerizing pages featuring cutting-edge innovations.

Immerse yourself in the magic of the Antari Snow Machine, transforming any space into a winter wonderland. Feel the breeze of excitement with the versatile Effect Fan, creating dynamic atmospheres with its powerful airflow.

Elevate your events with the whimsical charm of the Bubble Machine, adding a touch of playfulness to any occasion. Antari's Special Effect Page unveils a spectrum of possibilities, ensuring your gatherings are infused with enchantment.

Explore the pages and let the magic unfold with these extraordinary special effects.



❄️ S-600

CONTROL METHODS



MANUAL TIMER 5 PIN WIRELESS

OPTIONAL



W-DMX CABLE REMOTE

RATED POWER

> 1,200W

INCLUDED ACCESSORIES

- > W-2 Wireless Transmitter
- > 5-Meter Fluid Tube with Filter

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 10.0A
- > EU Model : AC 220-240V, 50/60Hz, 5.0A

FLUID CONSUMPTION

> 400 ml/min (100% Output)

COMPATIBLE FLUID

- > SL
- > SL-A
- > SL-AN
- > SL-C
- > SL-H
- > SL-N
- > SL-UV

DIMENSION

	L 462 mm	L 18.19 inch
	W 596 mm	W 23.47 inch
	H 630 mm	H 24.81 inch

WEIGHT

24.0 kg
52.90 lbs



Neutrik powerCON TURE 1
Connector Power



❄️ S-500

CONTROL METHODS	OPTIONAL	RATED POWER
------------------------	-----------------	--------------------

MANUAL
 TIMER
 3 PIN / 5 PIN

WIRELESS
 W-DMX
 CABLE REMOTE

> 900W

INCLUDED ACCESSORIES

- > S-500 : S-500-HOSE 10 Meter Standard Hose
- > S-500L : 500-HOSE 10 Meter Standard Hose + ST-10 10 Meter Extension Hose **Total 20 Meter**

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 7.5A
- > EU Model : AC 220-240V, 50/60Hz, 4.0A

FLUID CONSUMPTION

> 400 ml/min (100% Output)

COMPATIBLE FLUID

- > SL
- > SL-A
- > SL-AN
- > SL-C
- > SL-H
- > SL-N
- > SL-UV

WEIGHT
 S-500 : 37.2 kg 82.01 lbs
 S-500L : 46.4 kg 102.29 lbs

Neutrik powerCON Connector Power

DIMENSION

	L	W	H
S-500:	592 mm	551 mm	651 mm
	22.31 inch	21.69 inch	25.63 inch
S-500L:	803 mm	603 mm	651 mm
	31.61 inch	23.74 inch	25.63 inch

❄️ S-200X

CONTROL METHODS	OPTIONAL	RATED POWER
------------------------	-----------------	--------------------

MANUAL
 3 PIN

> N/A

> 880W

INCLUDED ACCESSORIES

- > SC-2 Cable Remote
- > Hanging Bracket

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 7.5A
- > EU Model : AC 220-240V, 50/60Hz, 4.0A

FLUID CONSUMPTION

> 140 ml/min (100% Output)

COMPATIBLE FLUID

- > SL
- > SL-A
- > SL-AN
- > SL-C
- > SL-H
- > SL-N
- > SL-UV

WEIGHT
 11.5 kg
 25.35 lbs

IEC Connector Power

DIMENSION

	L	W	H
S-200X:	505 mm	365 mm	409 mm
	19.88 inch	14.37 inch	16.10 inch



❄️ S-100X

CONTROL METHODS	OPTIONAL	RATED POWER
------------------------	-----------------	--------------------



 MANUAL 3 PIN

> N/A

> 880W

INCLUDED ACCESSORIES

- > SC-2 Cable Remote
- > Hanging Bracket

RATED VOLTAGE

- > US Model : AC100-120V, 50/60Hz, 7.5A
- > EU Model : AC 220-240V, 50/60Hz, 4.0A


FLUID CONSUMPTION

> 160 ml/min (100% Output)

COMPATIBLE FLUID

- > SL
- > SL-A
- > SL-AN
- > SL-C
- > SL-H
- > SL-N
- > SL-UV

DIMENSION

	L	505 mm	L	19.88 inch
	W	365 mm	W	14.37 inch
	H	409 mm	H	16.10 inch

WEIGHT

 11.0 kg
 24.25 lbs



❄️ SW-300

CONTROL METHODS	OPTIONAL	RATED POWER
------------------------	-----------------	--------------------





 MANUAL TIMER 5 PIN WIRELESS


 CABLE REMOTE

> 880W

INCLUDED ACCESSORIES

- > W-1 Wireless Transmitter
- > Hanging Bracket

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 7.5A
- > EU Model : AC 220-240V, 50/60Hz, 4.0A


FLUID CONSUMPTION

> 280 ml/min (100% Output)


COMPATIBLE FLUID

- > SL
- > SL-A
- > SL-AN
- > SL-C
- > SL-H
- > SL-N
- > SL-UV

DIMENSION

	L	513 mm	L	20.20 inch
	W	376 mm	W	14.81 inch
	H	349 mm	H	13.47 inch

WEIGHT

 11.5 kg
 25.35 lbs





❄️ SW-250



CONTROL METHODS **OPTIONAL** **RATED POWER**



> 900W

INCLUDED ACCESSORIES **RATED VOLTAGE**

- > W-1 Wireless Transmitter
- > Hanging Bracket

- > US Model : AC 100-120V, 50/60Hz, 8.0A
- > EU Model : AC 220-240V, 50/60Hz, 4.0A

FLUID CONSUMPTION **COMPATIBLE FLUID**

> 140 ml/min (100% Output)

- > SL > SL-C > SL-UV
- > SL-A > SL-H
- > SL-AN > SL-N

DIMENSION

	L	539 mm	L	21.22 inch
	W	365 mm	W	14.37 inch
	H	409 mm	H	16.10 inch

WEIGHT

11.5 kg
25.35 lbs



S T A G E / E N T E R T A I N M E N T
WHERE BUBBLE MAGIC MEETS ENDLESS FUN!

The Antari B Series is the epitome of bubble special effects, transforming any event into a mesmerizing spectacle. These professional-grade bubble machines deliver enchanting, glistening bubbles that captivate audiences of all ages. Crafted with precision and reliability, the B Series offers a range of models to suit any occasion, from intimate gatherings to grand stages. With whisper-quiet operation and adjustable output, you can create the perfect ambiance effortlessly. Designed for ease of use, they effortlessly integrate into your setup. Elevate your events, productions, and parties with the Antari B Series, where bubbles become magical moments that leave lasting memories.



B-100



W-101



B-100 / W-101



B-100 CONTROL METHODS



MANUAL

W-101 CONTROL METHODS



MANUAL



WIRELESS

RATED POWER

- > B-100 : 120V 30W / 240V 32W
- > W-101 : 120V 32W / 240V 32W

INCLUDED ACCESSORIES

- > B-100 : Hanging Bracket
- > W-101 : W-1 Wireless Transmitter Hanging Bracket

RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 0.5A
- > EU Model : AC 220-240V, 50/60Hz, 0.5A

FLUID CONSUMPTION

- > 8.3 ml/min (100% Output)

COMPATIBLE FLUID



> BL

DIMENSION

	L	W	H
B-100:	341 mm	265 mm	290 mm
	13.43 inch	10.44 inch	11.42 inch
W-101:	350 mm	264 mm	288 mm
	13.78 inch	10.40 inch	11.34 inch

WEIGHT

B-100 :	4.2 kg	9.26 lbs
W-101 :	4.8 kg	10.58 lbs

B-200

CONTROL METHODS



MANUAL



5 PIN

OPTIONAL



TIMER



WIRELESS



CABLE REMOTE

RATED POWER

- > 120W

INCLUDED ACCESSORIES

- > Hanging Bracket

RATED VOLTAGE

- > US Model : AC 100-120V, 50 / 60Hz 1.0A
- > EU Model : AC 220-240V, 50 / 60Hz 0.5A

FLUID CONSUMPTION

- > 50 ml/min

COMPATIBLE FLUID



> BL

DIMENSION

L	508 mm	L	20.00 inch
W	251 mm	W	9.89 inch
H	391 mm	H	15.40 inch

WEIGHT

	11.0 kg
	24.25 lbs



IEC Connector Power



STAGE / ENTERTAINMENT
MORE THAN A FAN – BLOW AWAY EXPECTATIONS!

Antari AF-Series Special Effect Fan: It's more than just a fan; it's a versatile blower designed to amplify your effects. Amplify your creative vision with increased wind power, intensifying the impact of various effects. Compatible with fog, haze, snow, foam, bubbles, and confetti, this fan is your ultimate tool for indoor and outdoor enchantment. However, please note that it's not suitable for rainy or wet conditions.

Elevate your experiences with the Antari AF-Series and harness the power of wind to breathe life into your artistic endeavors.



AF-6

CONTROL METHODS



MANUAL TIMER 5 PIN

OPTIONAL



WIRELESS CABLE REMOTE

RATED POWER

> 250W

INCLUDED ACCESSORIES

> N/A

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 2.5A
 > EU Model : AC 220-240V, 50/60Hz, 1.5A

DIMENSION

	L	462 mm	L	18.20 inch
	W	596 mm	W	23.50 inch
	H	630 mm	H	24.80 inch

WEIGHT

	22.3 kg
	49.10 lbs



Neutrik powerCON TURE 1
 Connector Power



AF-5X

CONTROL METHODS



MANUAL 5 PIN WIRELESS (AF-5XR)

OPTIONAL

> N/A

RATED POWER

> 1,600W

INCLUDED ACCESSORIES

> W-1 Wireless Transmitter (AF-5XR)

RATED VOLTAGE


> US Model : AC 100-120V, 50/60Hz, 13.5A
> EU Model : AC 220-240V, 50/60Hz, 7.0A

DIMENSION



L 558 mm L 21.97 inch
W 465 mm W 18.31 inch
H 578 mm H 22.76 inch

WEIGHT



17.5 kg
38.58 lbs

AF-4

CONTROL METHODS



MANUAL TIMER 5 PIN

OPTIONAL



WIRELESS (AF-4R) CABLE REMOTE

RATED POWER

> 100W


INCLUDED ACCESSORIES

> W-2 Wireless Transmitter (AF-4R)

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 1.0A
> EU Model : AC 220-240V, 50/60Hz, 0.5A

DIMENSION



L 353 mm L 13.90 inch
W 426 mm W 16.78 inch
H 517 mm H 20.35 inch

WEIGHT



9.0 kg
19.84 lbs



AF-3

CONTROL METHODS



MANUAL 5 PIN

OPTIONAL



WIRELESS CABLE REMOTE

RATED POWER

> 127W

INCLUDED ACCESSORIES

> N/A

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz, 1.5A
> EU Model : AC 220-240V, 50/60Hz, 1.0A

DIMENSION

	L	W	H
AF-3	124 mm	320 mm	371 mm
AF-3X	4.88 inch	12.59 inch	14.61 inch
AF-3S	160 mm	312 mm	337 mm
	6.29 inch	12.28 inch	13.27 inch

WEIGHT

AF-3	: 6.0 kg	13.23 lbs
AF-3X	: 6.0 kg	13.23 lbs
AF-3S	: 6.4 kg	14.00 lbs



Neutrik powerCON Connector Power

F I R E T R A I N I N G SAFETY IGNITES WITH TRAINING EXCELLENCE

The Antari FT Series, adorned in a striking red hue symbolizing the essence of fire. These fog machines are designed to create the thickest and most dense fog, offering an unparalleled training environment for fire fighters, search and rescue teams, and emergency responders. From mastering initial fire attack strategies to building mask confidence, the FT Series caters to diverse training needs, ensuring readiness for every conceivable scenario. With Antari, we understand that perfect training is the key to excellence, and our FT Series guarantees professionals are always prepared to excel in any situation.



FT-200

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 13.5A
- > EU Model : AC 220-240V, 50/60Hz, 7.0A

FLUID CONSUMPTION

- > 270 ml/min (100% Output)

DIMENSION

	L	301 mm	L	11.85 inch
	W	195 mm	W	7.68 inch
	H	414 mm	H	16.30 inch

OPTIONAL



RATED POWER

- > 1,600W

COMPATIBLE FLUID



WEIGHT

	16.0 kg
	35.28 lbs

INCLUDED ACCESSORIES

- > W-2 Wireless Transmitter



Neutrik powerCON TRUE1
Connector Power

FT-100

CONTROL METHODS



RATED VOLTAGE

- > US Model : AC 100-120V, 50/60Hz, 13.0A
- > EU Model : AC 220-240V, 50/60Hz, 6.5A

FLUID CONSUMPTION

- > 100 ml/min (100% Output)

DIMENSION

	L	580 mm	L	22.84 inch
	W	279 mm	W	10.99 inch
	H	331 mm	H	13.03 inch

OPTIONAL



RATED POWER

- > 120V 1,500W
- > 240V 1,450W

COMPATIBLE FLUID



WEIGHT

	14.6 kg
	32.19 lbs

INCLUDED ACCESSORIES

- > W-2 Wireless Transmitter



Neutrik powerCON
Connector Power



FT-70

CONTROL METHODS



MANUAL WIRELESS

OPTIONAL

> N/A

INCLUDED ACCESSORIES

> W-3 Wireless Transmitter

RATED VOLTAGE

> US Model : AC 100-120V, 50/60Hz 8.5A
> EU Model : AC 220-240V, 50/60Hz 4.5A

RATED POWER

> 1,000W

FLUID CONSUMPTION

> 60 ml/min (100% Output)

COMPATIBLE FLUID




> FLP

DIMENSION



L 417 mm L 16.42 inch
W 178 mm W 7.01 inch
H 273 mm H 10.75 inch

WEIGHT



7.0 kg
15.43 lbs



IEC Connector Power

FT-20X

CONTROL METHODS



MANUAL 3PIN

OPTIONAL



WIRELESS

CABLE REMOTE

INCLUDED ACCESSORIES

> FLM-05P Fog Fluid 500ml
> FFT-20 Flighcase
> FT-20X-B Battery
> FT-20-BCL Charger

RATED VOLTAGE

> DC 12V (Battery)
> AC 100-240V, 50/60Hz (Battery Charger)

RATED POWER

> 600W

FLUID CONSUMPTION

> 16 ml/min (100% Output)

COMPATIBLE FLUID



> FLM-05P

DIMENSION



L 293 mm L 11.54 inch
W 108 mm W 4.26 inch
H 239 mm H 9.41 inch

WEIGHT



8.5 kg
18.74 lbs



PROFESSIONAL SCENT SOLUTIONS FOR EVERY SPACE

The Antari SCN Series redefines ambiance by delivering immersive aromatic experiences for professional, commercial, and residential environments. Designed for versatility, it ensures consistent and even diffusion, enhancing atmospheres in any environment. With sleek, modern aesthetics and whisper-quiet performance, the SCN Series seamlessly integrates into any setting while offering customizable intensity levels to suit diverse needs. Built for durability and efficiency, the SCN Series offers a perfect blend of functionality and sophistication, redefining how spaces connect with their audiences.

ARO-01-203 :

Blend of Essential Oils:
 Top Notes: Pink Grapefruit, Juniper Berry
 Middle Notes: Bourbon Geranium, Lavandula Angustifolia (Lavender)
 Base Notes: Patchouli

ARO-01-701 :

Blend of Essential Oils:
 Juniperus squamata var. morrisonicola/
 Chamaecyparis formosensis(Hinoki)

ARO-01-209 :

Blend of Essential Oils:
 Top Notes: Pink Grapefruit, Lime
 Middle Notes: Camphor
 Base Notes: Rosewood

ARO-01-501 :

Blend of Essential Oils:
 Top Notes: Sweet Orange, Lemongrass, Lime
 Middle Notes: Eucalyptus, Lavender, Citronella
 Base Notes: Cypress(Hinoki)



ARO-01-203



ARO-01-209



ARO-01-701



ARO-01-501



SCN-600

CONTROL METHODS



RATED VOLTAGE

> AC 100-240V, 50 / 60 Hz 0.5A

OPTIONAL

> N/A

INCLUDED ACCESSORIES

> N/A

RATED POWER

> 7W

FLUID CONSUMPTION

> 1 ml/hour (100% Output)

COMPATIBLE FLUID

> ARO-01-203 > ARO-01-701
 > ARO-01-209
 > ARO-01-501

DIMENSION

L	267 mm	L	10.5 inch
W	115 mm	W	4.52 inch
H	222 mm	H	8.74 inch

WEIGHT

3.2 kg
 7.05 lbs



IEC Connector Power

U V E F F E C T S INTRO

The prodigious DarkFX Series has adopted the latest LED technology with a peak wavelength of 365nm. Because, 365nm is in the middle of UV-A wavelength the emitted light evenly covers the whole spectrum producing a traditional blacklight effect without the visible light associated with most LED based blacklights. All UV reactive material reflects perfectly with stunning bright and vivid colors.

Traditional blacklight fixtures emit long-wave ultraviolet (UV) light without much visible light. The UV spectrum ranges from 100 to 400 nanometers (nm), emitting light that is generally invisible to the human eye*, however the higher the “nm” rating the more visible light. Traditionally the entertainment industry has used the UV-A spectrum (315-400nm), which is not harmful to humans, widely adopted in light fixtures, counterfeit detection, medical use and industrial curing.



*Typical human eye will respond to wavelength from 390 to 700nm



DARKFX STRIP 1020

FEATURES



- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Minimum visible light
- › High output 9,000mW at full intensity
- › Special optics will not degrade by high UV exposure
- › Flicker free

- › Dimension L 1194 W 46 H 101 mm
L 47.00 W 1.82 H 3.98 inch
- › Dry Weight 1.9 kg
4.18 lbs

SPECIFICATION

- › Rated Voltage DC 48V @ 0.5A
- › Rated Power 24W
- › Light Source 12 x 1.9W High Power UV LED
- › Optics 40 degrees
- › Radiant Flux Output 9,000 mW
- › Project Lamp Life 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°C-40°C(32°F-104°F)
- › Cable Connection 22 AWG Wire Cable
- › Housing Aluminum Extrusion
- › Protection Rating IP-20 Indoor Use Only

SPECTRUM



ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	450 (μW/cm ²) 4.5 (W/m ²)	158 (μW/cm ²) 1.58 (W/m ²)	79 (μW/cm ²) 0.79 (W/m ²)	42 (μW/cm ²) 0.42 (W/m ²)	31 (μW/cm ²) 0.31 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	64.9%	82.5%	90.7%	93%



DARKFX STRIP 510



FEATURES



- High efficiency UV LED
- Peak wavelength at 365nm
- Minimum visible light
- High output 4,500mW at full intensity
- Special optics will not degrade by high UV exposure
- Flicker free

SPECIFICATION

- Rated Voltage DC 20-24V
- Rated Power 12W
- Light Source 6 x 1.9W High Power UV LED
- Optics 25 degrees
- Radiant Flux Output 4,500 mW
- Project lamp life 20,000 hrs L70 at 25°C
- Peak wavelength 365nm
- Ambient Temp. Range 0°-40°C(32°F-104°F)
- Cable connection 22 AWG Wire Cable
- Housing Aluminum Extrusion
- Protection rating IP-20 Indoor Use Only

- Dimension L 594 x W 46 x H 101 mm
L 23.39 W 1.82 H 3.98 inch
- Dry Weight 1.9 kg
4.18 lbs

SPECTRUM



ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	700 (μW/cm ²) 7.00 (W/m ²)	211 (μW/cm ²) 2.11 (W/m ²)	99 (μW/cm ²) 0.99 (W/m ²)	54 (μW/cm ²) 0.54 (W/m ²)	38 (μW/cm ²) 0.38 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	69.6%	85.9%	92.2%	94.5%

DARKFX STRIP 510 IP



FEATURES



- High efficiency UV LED
- Peak wavelength at 365nm
- Minimum visible light
- High output 4500mW at full intensity
- Special optics will not degrade by high UV exposure
- Flicker free

SPECIFICATION

- Rated Voltage DC 20-24V
- Rated Power 12W
- Light Source 6 x 1.9W High Power UV LED
- Optics 25 degrees
- Radiant Flux Output 4,500 mW
- Lige Span 20,000 hrs L70 at 25°C
- Peak Wavelength 365nm
- Ambient Temp. Range 0°-40°C(32°F-104°F)
- Cable Connection 22 AWG Wire Cable
- Housing Aluminum Extrusion
- Protection Rating IP-65

- Dimension L 606 W55 H100 mm
L23.86 W 2.17 H3.94 inch
- Dry Weight 1.1 kg
2.42 lbs

SPECTRUM



ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	700 (μW/cm ²) 7.00 (W/m ²)	211 (μW/cm ²) 2.11 (W/m ²)	99 (μW/cm ²) 0.99 (W/m ²)	54 (μW/cm ²) 0.54 (W/m ²)	38 (μW/cm ²) 0.38 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	69.8%	85.9%	92.2%	94.5%



DARKFX WASH 2000 IP



DARKFX WASH 2000

FEATURES

- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Special optics will not degrade to high UV exposure
- › Minimum visible light
- › High output 24,800 mW at full intensity
- › Flicker free

- › Housing Aluminum Die-Cast
- › Protection Rating IP-65
- › Dimension L 454 W 116 H 331 mm
L 17.87 W 4.56 H 3.03 inch
- › Dry Weight 10.4 kg
22.92 lbs

SPECTRUM



SPECIFICATION

- › Rated Voltage AC 100-240V, 50/60Hz
- › Rated Power 70W
- › Light Source 33 x 1.9W High Power UV LED
- › Refresh Rate 500Hz
- › Optics 25 degrees
- › Radiant Flux Output 24,800 mW
- › Life Span 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°-40°C (32°F-104°F)
- › Control Manual, DMX512
- › DMX Channels 2 Channel
- › Connection Neutrik powerCON (Power)
XLR-5 PIN (DMX)

ILLUMINANCE MEASUREMENT



Distance(m)	1	2	3	4	5
Intensity	5462 (μW/cm ²) 54.62 (W/m ²)	1572 (μW/cm ²) 15.72 (W/m ²)	718 (μW/cm ²) 7.18 (W/m ²)	4.09 (μW/cm ²) 4.09 (W/m ²)	251 (μW/cm ²) 2.51 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	71.2%	86.8%	92.5%	95.4%

FEATURES

- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Minimum visible light
- › High output 20,290 mW at full intensity
- › Special optics will not degrade by high UV exposure
- › Flicker free
- › Adjustable modularstrips to maximize coverage

- › Protection Rating IP-20 Indoor Use Only
- › Dimension L 600 W 182 H 182 mm
L 23.62 W 7.17 H 7.17 inch
- › Dry Weight 6.4 kg
14.10 lbs

SPECTRUM



SPECIFICATION

- › Rated Voltage AC 100-240V, 50/60Hz
- › Rated Power 55W
- › Light Source 27 x 1.9W High Power UV LED
- › Refresh Rate 500Hz
- › Optics 25 degrees
- › Radiant Flux Output 20,290 mW
- › Life Span 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°-40°C(32°F-104°F)
- › Control Manual, DMX512
- › DMX Channels 2 Channel
- › Connection Neutrik powerCON (Power)
XLR-5 PIN (DMX)
- › Housing Metal

ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	4184 (μW/cm ²) 41.84 (W/m ²)	1737 (μW/cm ²) 17.37 (W/m ²)	933 (μW/cm ²) 9.33 (W/m ²)	648 (μW/cm ²) 6.48 (W/m ²)	526 (μW/cm ²) 5.26 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	66.3%	83.8%	87.7%	90.9%



DARKFX SPOT 1750

FEATURES



- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Minimum visible light
- › High output 19,080 mW at full intensity
- › Special optics will not degrade by high UV exposure
- › Flicker free
- › 15 degrees narrow beam angle

SPECIFICATION

- › Rated Voltage AC 100-240V, 50/60Hz
- › Rated Power 72W
- › Light Source 4 X 16W High Power UV LED
- › Refresh Rate 600 Hz
- › Optics 20 degrees
- › Radiant Flux Output 19,080 mW
- › Life Span 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°-40°C(32°F-104°F)
- › Control Manual DMX512
- › DMX Channels 2 Channels
- › Connection Neutrik powerCON (Power) XLR-5 PIN (DMX)

- › Housing Metal
- › Protection Rating IP-20 Indoor Use Only
- › Dimension L 235 W 197 H 248 mm
- › Dry Weight 3.2 kg 7.06 lbs

SPECTRUM



ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	6573 (μW/cm ²) 65.73 (W/m ²)	1760 (μW/cm ²) 17.6 (W/m ²)	769 (μW/cm ²) 7.69 (W/m ²)	43.9 (μW/cm ²) 4.39 (W/m ²)	38 (μW/cm ²) 0.38 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	73.2%	88.3%	93.3%	95.6%



DARKFX SPOT 670

FEATURES



- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Minimum visible light
- › High output 6,760 mW at full intensity
- › Special optics will not degrade by high UV exposure
- › Flicker free
- › 15 degrees narrow beam angle

SPECIFICATION

- › Rated Voltage AC 100-240V, 50/60Hz
- › Rated Power 21W
- › Light Source 9 x 1.9W High Power UV LED
- › Refresh Rate 500Hz
- › Optics 15 degrees
- › Radiant Flux Output 6,760 mW
- › Life Span 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°-40°C(32°F-104°F)
- › Control Manual DMX512
- › DMX Channels 2 Channel
- › Connection Neutrik powerCON (Power) XLR-5 PIN (DMX)

- › Housing Metal
- › Protection Rating IP-20 Indoor Use Only
- › Dimension L 205 W 191 H 210 mm
- › Dry Weight 2.7 kg 5.95 lbs

SPECTRUM



ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	4976 (μW/cm ²) 49.76 (W/m ²)	1675 (μW/cm ²) 16.75 (W/m ²)	807 (μW/cm ²) 8.07 (W/m ²)	614 (μW/cm ²) 6.14 (W/m ²)	451 (μW/cm ²) 4.51 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	66.3%	83.8%	87.7%	90.9%



DARKFX SPOT 510 IP





FEATURES

- › High efficiency UV LED
- › Peak wavelength at 365nm
- › Minimum visible light
- › High output 4,500 mW at full intensity
- › Special optics will not degrade by high UV exposure
- › Flicker free

› Dry Weight 0.8 kg
1.76 lbs

SPECTRUM



SPECIFICATION

- › Rated Voltage DC 20-24V
- › Rated Power 12W
- › Light Source 6 x 1.9W High Power UV LED
- › Optics 15 degrees
- › Radiant Flux Output 4,500 mW
- › Life Span 20,000 hrs L70 at 25°C
- › Peak Wavelength 365nm
- › Ambient Temp. Range 0°-40°C (32°F-104°F)
- › Cable Connection 22 AWG Wire Cable
- › Housing Aluminum Extrusion
- › Protection Rating IP-65
- › Dimension L 119 W 66 H 135 mm
L 4.69 W 2.60 H 5.32 inch

ILLUMINANCE MEASUREMENT

Distance(m)	1	2	3	4	5
Intensity	2062 (µW/cm ²) 20.62 (W/m ²)	534 (µW/cm ²) 5.34 (W/m ²)	213 (µW/cm ²) 2.13 (W/m ²)	126 (µW/cm ²) 1.26 (W/m ²)	76 (µW/cm ²) 0.76 (W/m ²)
Intensity degradation rate (Compare with 1m)	0%	74.1%	89.6%	93.9%	96.3%

DARKFX DRIVE 4 MKII




FEATURES

- › Compact and robust design
- › 4 Output terminals for DARKFX UV fixtures
- › Neutrik powercon in/ thru
- › 2 x 16 digit lcd display interface
- › DMX control option
- › RDM feature set

SPECIFICATION

- › Rated Voltage AC 100-240V, 50/60Hz
- › Rated Power 100W
- › Output Current DC12-48V Constant 500mA
Max. Per Channel
- › Refresh rate 600 Hz
- › Ambient Temp. Range 0°-40°C(32°F-104°F)
- › Fixture Output 4 Terminal Block
- › Control Manual
DMX 512
- › DMX Channels 2 Channel
- › Connection Neutrik Powercon (Power)
XLR 5-pin (DMX)
- › Housing Metal
- › Protection Rating IP-20 Indoor Use Only
- › Dimension L 216 W 167 H 71 mm
L 8.50 W 6.58 H 2.80 inch
- › Weight 1.7 kg
3.58 lbs



A C C E S S O R I E S



LCU-2S

CONTROL



AUTO

INCLUDED ACCESSORIES

- > XLR 3-Pin Data Cable
- > 12 Meter 6mm x 4mm Tube
- > 10Meter 6mm x 4mm Tube
- > 4 to 4mm Adaptor x3
- > 6 to 4mm Adaptor x3
- > Fluid Filter

RATED VOLTAGE

- > US Model : AC 100 - 120V, 50 / 60 Hz 0.5A
- > EU Model : AC 220 - 240V, 50 / 60 Hz 0.5A

RATED POWER

- > 55W

FLUID CONSUMPTION

- > N/A

FLUID

- > Antari Fluid

DIMENSION

	Supply Unit		Tank Unit	
L	179 mm	7.05 inch	158 mm	6.22 inch
W	168 mm	6.62 inch	103 mm	4.06 inch
H	84 mm	3.31 inch	312 mm	12.29 inch

WEIGHT

	Supply Unit	Tank Unit
	2.0 kg	1.8 kg
	4.40 lbs	3.97 lbs



IEC
Connector
Power



LCU-1S

CONTROL



MANUAL



TIMER



3PIN

INCLUDED ACCESSORIES

- > XLR 4-Pin Data Cable
- > 10 Meter 4mm x 2.5mm Tube
- > FTA-64 Adapter (6mm to 4mm)
- > Fluid Filter

RATED VOLTAGE

- > US Model : AC 100 - 120V, 50 / 60 Hz 0.5A
- > EU Model : AC 220 - 240V, 50 / 60 Hz 0.5A

RATED POWER

- > 40W

FLUID CONSUMPTION

- > 400 ml/min (100% Output)

FLUID

- > Antari Fluid

DIMENSION

	L	W	H	L	W	H
L	203 mm	179 mm	96 mm	7.99 inch	7.05 inch	3.78 inch

WEIGHT

	3.3 kg
	7.28 lbs



IEC
Connector
Power



W-1

WORKING DISTANCE:
Up to 50 m (164 ft)

FREQUENCY:
315 MHz & 433 MHz

COMPATIBLE WITH:
AF-3R, AF-3XR, AF-5XR, F-1, HZ-350, SW-250, SW-300, W-508



W-2

WORKING DISTANCE:
Up to 50 m (164 ft)

FREQUENCY:
315 MHz & 433 MHz

COMPATIBLE WITH:
AF-4R, AF-6, F-6, F-7X, F-12, FT-20X, FT-100, FT-200,
IP-1600, IP-3000, M-7X, M-9, M-12, MB-20X, S-500, S-600,
Z-390, Z-1520, Z-1500III, Z-3000III



W-3

WORKING DISTANCE:
Up to 50 m (164 ft)

FREQUENCY:
315 MHz & 433 MHz

COMPATIBLE WITH:
FT-70

EASY SWITCH



ES-W2-RECEIVER

ES-W-DMX

RECEIVER



W-1 RECEIVER

W-2 RECEIVER



TIMO-W-DMXW1R
W-DMX & W-1 RECEIVER

TIMO-W-DMXW2R
W-DMX & W-2 RECEIVER



TIMO-W-DMX-PCB

TIMO-W-DMXR
W-DMX RECEIVER


Wireless Working Distance May Vary
Depending on the Interference



WTR-120
› W-3 Transmitter
› W-2 Receiver



TIMO-WTR-50
› W-1 Transmitter
› TIMO-W-DMXW1R



WTR-110
› W-2 Transmitter
› ES-W-2 Receiver



TIMO-WTR-40
› W-1 Transmitter
› TIMO-W-DMXW1R
› TIMO-W-DMX-PCB



WTR-90
› TIMO-W-DMX-PCB
› TIMO-W-DMXW2R



WTR-20
› W-2 Transmitter
› W-2 Receiver



TIMO-WTR-80
› W-2 Transmitter
› TIMO-W-DMXW2R



WTR-10
› W-1 Transmitter
› W-1 Receiver



TIMO-WTR-70
› W-2 Transmitter
› TIMO-W-DMXW2R
› TIMO-W-DMX-PCB



TIMO-W-DMX-PCBR
› TIMO-W-DMX-PCB
› TIMO-W-DMXR



WTR-60
› TIMO-W-DMX-PCB
› TIMO-W-DMXW1R

WTR-10	WTR-20	TIMO-WTR-40_50_60
AF-3, F-1, SW-250X	AF-4R, AF-6, FT-20X, MB-20X, S-500(L), Z-390, Z-1500III, Z-3000III	F-1

TIMO-WTR-70_80	TIMO-WTR-90	WTR-110	WTR-120	TIMO-W-DMX-PCBR
S-500(L)	M-7X, M-9, S-500(L), S-600	F-6, F-7X, F-12, M-12	FT-70	CH-1, F-1, S-500(L)

M-20



- › Compatible Model : M-5, M-10
- › Cable Length : 2M
- › Connector : 5 PIN XLR

M-21



- › Compatible Model : M-8
- › Cable Length : 2M
- › Connector : 5 PIN XLR

M-30PRO



- › Compatible Model : M-5, M-10
- › Working Distance : Up to 50 m
- › Connector : 5 Pin XLR



M-31



- › Compatible Model : M-8
- › Working Distance : Up to 50 m
- › Connector : 5 Pin XLR



Z-3

REMOTE

- › Compatible Model : AF-3, AF-4, FT-20X, FT-100, FT-200,
- › MB-20X, Z-350, Z-390, Z-1200III
- › Cable Length : 9 ft
- › Connector : 1/4 Stereo



Z-8

TIMER REMOTE

- › Compatible Model : ICE-101, LCU-1S
- › Cable Length : 25 ft
- › Connector : 4 PIN XLR



Z-10

REMOTE

- › Compatible Model : Z-800III, Z-1000III
- › Working Distance : 25 ft
- › Connector : 1/4 Stereo



Z-40

TIMER REMOTE

- › Compatible Model : Z-800III, Z-1000III, Z-1200III
- › Cable Length : 25 ft
- › Connector : 1/4 Stereo

Wireless Working Distance May Vary Depending on the Interference



Z-50

WIRELESS REMOTE



- › Compatible Model : Z-800III, Z-1000III, Z-1200III
- › Working Distance : Up to 50 m
- › Connector : 1/4 Stereo



BGR-1

WIRELESS REMOTE



- › Compatible Model : B-200
- › Working Distance : Up to 50 m
- › Connector : 1/4 Stereo

BCT-1

WIRELESS REMOTE



- › Compatible Model : B-200
- › Cable Length : 25ft
- › Connector : 1/4 Stereo

HC-1

TIMER REMOTE



- › Compatible Model : HZ-100, HZ-350, HZ-400
- › Cable Length : 25 ft
- › Connector : 1/4 Stereo



HGR-1

WIRELESS REMOTE



- › Compatible Model : HZ-100, HZ-400
- › Working Distance : Up to 50 m
- › Connector : 1/4 Stereo

MGR-1F

WIRELESS REMOTE



- › Compatible Model : MB-1
- › Working Distance : Up to 50 m
- › Connector : 4 PIN DIN

MGT-2

TIMER REMOTE



- › Compatible Model : MB-1
- › Cable Length : 25ft
- › Connector : 4 PIN DIN

SC-2

REMOTE



- › Compatible Model : AF-6, LCU-1S, S-100X, S-200X, SW-250(X)
- › Cable Length : 25 ft
- › Connector : 4 PIN XLR

SC-3 REMOTE



- › Compatible Model : SW-300, S-500(L)
- › Cable Length : 25 ft
- › Connector : 4 PIN XLR

SC-4 REMOTE




- › Compatible Model : S-600
- › Cable Length : 25 ft
- › Connector : 6 PIN XLR


HANGING BRACKET SET

M-9-HB

One M-9 requires 2 pcs
M-9-HB




M-5-HB M-5, M-8



SW-300-FB

Floor Bracket
S-100X, S-200X
SW-250(X), SW-300




FLUID TUBE & FILTER



FT-4
4mm fluid tube
FT-6
6mm fluid tube



FLF-4
Fluid filter for 4mm tube
FLF-6
Fluid filter for 6mm tube



FTA-64
Adaptor for 4mm to 6mm tube connection
FTA-66
Adaptor for 6mm to 6mm tube connection
FTA-664
Adaptor for two 6mm tubes to one 4mm tube connection

REMOTE CONTROL EXTENSION CABLES



EXT-1
25 ft. extension cable with 1/4 stereo plug



EXT-3
25 ft. extension cable
with 5-pin XLR connectors

EXT-4
25 ft. extension cable
with 3-pin XLR connectors

EXT-6
25 ft. extension cable
with 4-pin XLR connectors



EXT-5
25 ft. extension cable
with 5-pin XLR connectors

ADAPTORS



FTA-1

Adaptor for connecting fog conducting hose FT-10 to FT-100, IP-160Q, IP-300Q, M-5, M-8, M-10, Z-1500III & Z-3000III fog machines. in order to achieve strategic fog placement.



FTA-2A

The same function as the FTA-1, specifically designed for FT-70, Z-1000III & Z-1200III fog machine.



FTA-200

Fog conducting hose adaptor for and DNG-250. The hose adaptor can be installed on it and this can split fog output into two.



FTA-11

Fog conducting hose adaptor for and DNG-100. The hose adaptor can be installed on it and this can split fog output into two.



FT-10

Fog conducting hose for DNG-100 with 12 cm diameter and 10 meters in length

FLIGHT CASE



FCH-1

Dimensions : L900 W 574 H 938 mm
Weight : 51.6 kg
Compatible With : CH-1



FDNG-250

Dimensions : L865 W 695 H 1020 mm
Weight : 46.5 kg
Compatible With : DNG-250



FZ-350

Dimensions : L429 W 230 H 478 mm
Weight : 8.9 kg
Compatible With : Z-350



FX-4

Dimensions : L495 W 418 H 500 mm
Weight : 12.3 kg
Compatible With : Z-1520, Z-350
- Two unit in the case



FX-6

Dimensions : L730 W 453 H 425 mm
Weight : 12.3 kg
Compatible With : F-1, S-100X, S-200X, SW-250(X), SW-300


FLUID



Welcome to the Antari Fluid Page. Your gateway to premium atmospheric effects, our Fog Fluid, formulated with Propylene Glycol aka PG, guarantees a safe and mesmerizing mist. Antari Snow Fluid transforms your surroundings into a winter wonderland, while Bubble Fluid adds a playful touch to any event.

Crafted from pharmaceutical-grade raw materials, our fluids ensure the highest quality and performance. Versatile and compatible with all Antari machines, these fluids promise a seamless and exceptional experience.

Explore the pages to discover how Antari sets the standard for excellence in fluid technology, enhancing your events with captivating and reliable special effects.



	0.5L	EU 1L	1L	1L	2.5L	4L	5L	EU 5L	6L	10L	20L	200L
FLG	-	▲	-	▲	▲	▲	▲	▲	▲	▲	▲	▲
FLH	-	-	-	▲	-	▲	▲	▲	-	▲	▲	▲
FLJ	-	-	-	▲	-	▲	▲	-	-	-	▲	▲
FLR	-	-	-	▲	▲	▲	▲	-	▲	▲	▲	▲
FLY	-	-	-	▲	▲	▲	▲	-	▲	-	▲	▲
FLZ	-	-	-	▲	-	▲	▲	▲	-	-	▲	▲
FLL	-	-	-	▲	-	▲	▲	▲	▲	▲	▲	▲
FLC	-	-	-	▲	-	▲	▲	-	-	▲	▲	▲
FLM-P	▲	-	-	-	-	-	▲	-	-	-	▲	-
FLM-S	▲	-	-	-	-	-	-	-	-	-	-	-
SL-CNT	-	▲	-	-	-	-	-	-	-	▲	-	-
SL-UV	-	-	-	▲	-	▲	▲	-	-	-	▲	▲
SL-N	-	-	-	▲	-	-	▲	-	-	-	▲	▲
SL-H	-	-	-	▲	-	▲	▲	-	-	-	▲	▲
SL-C	-	-	-	▲	-	▲	▲	-	-	-	▲	▲
SL-AN	-	-	-	▲	-	▲	▲	-	-	-	▲	▲
SL-A	-	-	-	-	-	-	▲	-	-	-	▲	▲
SL	-	-	-	-	-	-	▲	-	-	-	▲	▲
FLP	-	-	-	▲	-	▲	-	-	▲	-	▲	▲
HZL-W	-	-	▲	-	-	▲	▲	-	-	-	▲	▲
HZL	-	-	▲	-	▲	▲	▲	-	-	-	▲	▲
BL	-	-	-	▲	-	▲	▲	-	-	-	▲	-



FLG
Regular Dense &
Regular Dissipating Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLH
Extremely Thin &
Fast Dissipating Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLJ
Extremely Thin &
Extremely Fast Dissipating Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLR
Extra Dense &
Extremely Fast Dissipating Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLY
Extremely Dense &
Extremely Long Lasting Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLZ
Super Dense &
Super Long Lasting Fog Fluid

DENSITY LIGHT HEAVY

DISSIPATION FAST SLOW



FLL Low Fog Fluid
FOR ICE-101/ DNG-250 USE ONLY



FLC Jet Fog Fluid
FOR JET FOG MACHINE USE ONLY



BL Bubble Fluid
› Water-based composition that creates vivid, transparent bubble.
FOR B-100/B-200/W-101 USE ONLY

SNOW FLUID



2025 NEW

SL-CNT

- › Snow Fluid Concentrate.
- › Must Diluted before Use.



SL-UV UV Snow Fluid

SnowFlake Blizzard

- › Produced UV Effect Snowflake that glows in the dark with UV light sources.



SL-C Antifreeze Snow Fluid

SnowFlake Blizzard

- › Antifreeze Snow Fluid for low temperature environments up to -10°C (14°F).



SL-H Super Dry Snow Fluid

SnowFlake Blizzard

- › Produce the largest volume and driest snowflakes.



SL-AN Extra Dry Snow Fluid

SnowFlake Blizzard

- › Produce slightly larger snowflakes than SL-A.



SL-N Superior Snow Fluid

SnowFlake Blizzard

- › Most popular snow fluid
- › Produce slightly larger snowflakes than SL.



SL-A Premium Snow Fluid

SnowFlake Blizzard

- › Produce slightly larger snowflakes than SL-N.



SL Regular Snow & Foam Fluid

SnowFlake Blizzard

- › Mildest Formula for Snow Effect & Foam Effect.

FIRE TRAINING FOG FLUID



FLM-05P

FLM-05P is a special formulated water based fluid for battery operated machine. Capable to generate pure and clean fog.

Special Formulated for FT-20X USE ONLY



FLP

Antari FLP fog fluid is specifically made for fire training machine.

FLP FOR FT-70 / FT-100 / FT-200 USE ONLY



FLM-05P

Light Fog Fluid

> FLM-05P is a special formulated water based fluid for battery operated machine. Capable to generate pure and clean fog.

Special Formulated for MB-20X USE ONLY



FLM-05S

Light Fog Fluid

> FLM-05S is a special formulated water based fluid for battery operated machine. Capable to generate pure and clean fog.

Special Formulated for MB-1 USE ONLY



HZL-1

Oil-Based Haze Fluid

> Special formulated haze fluid, a non toxic composition that produces a pure, translucent haze effect with a long hanging time.



HZL-1W

Water-Based Haze Fluid

> Special formulated haze fluid, it produces a smooth haze effect without greasy residue.

Only Compatible with Antari HZ Series: HZ-100/HZ-350/HZ-400/HZ-500/HZ-1000



CHL-2

> Special formulated Oil-Based Haze Fluid specifically for CH-1

FOR CH-1 USE ONLY




MG-550 MAGICAN

> The smallest haze spray in the world
> 1 - 2 hrs hang time
> Visual effect after 20 sec.
> Perfect for Mobile DJs and Home Parties



C-300 PUMP CLEANER

> Specially formulated for pump maintenance.
> Applying on regular basis to keep the pump at its optimal condition.
> Recommend use it before store machines.



UVL-01 UV AGENT

> For all Snow / Bubble fluid.
> Mix 1 bottle(100ml) with 5L of snow/ bubble fluid.
> Must use with a UV source to visual the effect.

SCENT

Simply put a few drops of these high quality scent into the fluid tank. You will have scented fog right away! 6 fragrances are available in a standard 20 ml bottle. The ideal mix ratio of scent and fluid is 1:1000 For instance: adding 1ml scent into 1liter fog fluid can have the best effect of scented fog.

Note : Mix with fog fluid only



P-9
ORANGE

P-7
STRAWBERRY

P-6
LEMON

P-4
APPLE

P-2
MINT

P-1
ROSE

ACCESSORIES LIST



FOG

OPTIONAL

Z-800III	<ul style="list-style-type: none"> > Z-10 > Z-40 > Z-50
Z-1000III	<ul style="list-style-type: none"> > Z-10 > Z-1000III-HB > Z-40 > Z-50
Z-1200III	<ul style="list-style-type: none"> > Z-1000III-HB > Z-3 > Z-40 > Z-50
Z-1500III Z-3000III	<ul style="list-style-type: none"> > WTR-20
M-5	<ul style="list-style-type: none"> > M-20 > M-30PRO > M-5-HB
M-10	<ul style="list-style-type: none"> > M-20 > M-30PRO

M-8	<ul style="list-style-type: none"> > M-21 > M-31 > M-5-HB
M-12	<ul style="list-style-type: none"> > WTR-110 > ES-W-DMX > M-12-HB
W-508	<ul style="list-style-type: none"> > W-1
IP-1600 IP-3000	<ul style="list-style-type: none"> > W-2 > IP-1600-HB
M-9	<ul style="list-style-type: none"> > W-2 > TIMO-WTR-90 > M-9-HB
M-7X	<ul style="list-style-type: none"> > W-2 > TIMO-WTR-90
Z-1520	<ul style="list-style-type: none"> > W-2 > FX-4
CH-1	<ul style="list-style-type: none"> > PRESSURE GAUGE AIR HOSE > TIMO-W-DMX-PCB > FCH-1 - AF-3S FAN TO FIT IN - FCH-1 FIGHT CASE

PORTABLE FOG MACHINE

MB-1	<ul style="list-style-type: none"> > FIGHT CASE > BAT-01 > MB-1-BCL > FLM-05S > DCP-12 - POWER ADAPTOR - DUMMY BATTERY > MCT-2 > MCR-1F
MB-20X	<ul style="list-style-type: none"> > FIGHT CASE > MB-20X-B > MB-20X-BCL > FLM-05P > Z-3 > WTR-20 > MB-20XS

FAZE

F-1	<ul style="list-style-type: none"> > TIMO-W-DMX-PCBR > WTR-10 > TIMO-WTR-40
F-6	<ul style="list-style-type: none"> > WTR-110 > ES-W-DMX

OPTIONAL

F-7X	<ul style="list-style-type: none"> > WTR-110 > ES-W-DMX > WTR-110
F-12	<ul style="list-style-type: none"> > ES-W-DMX
Z-350	<ul style="list-style-type: none"> > Z-3 CABLE > FZ-350 > FX-4
Z-390	<ul style="list-style-type: none"> > Z-3 > WTR-20

HAZER

HZ-100	<ul style="list-style-type: none"> > HC-1 > HCR-1
HZ-350	<ul style="list-style-type: none"> > W-1 > HC-1
HZ-400	<ul style="list-style-type: none"> > HC-1 > HCR-1
HZ-1000	<ul style="list-style-type: none"> > TIMO-W-DMX-PCBR

ACCESSORIES LIST



LOW FOG

OPTIONAL

	> FT-10
	> FTA-11
	> CODNG0600
	> FDNG-250
	> FTA-200
	> CODNG0600
	> Z-8

SNOW

	> SC-2
	> S-100X-HB
	> S-200X-HB
	> SW-300-FB
	> W-1
	> SW-250-HB
	> SC-2
	> SW-300-FB
	> W-1
	> SW-300-HB

	> SC-3
	> SW-300-FB
	> ST-500-HOSE
	S-500 INCLUDED
	> ST-10
	- S-500L INCLUDED
	- S-500 OPTIONAL
	> TIMO-W-DMX-PCBR
	> WTR-20
	> TIMO-WTR-70
	> SC-3
	> PM-1
	> W-2
	> 5 METER FLUID
	> TIMO-WTR-90
	> SC-4 CABLE REMOTE
	> S-600-BH
	> S-600-TKC

FAN

	> WTR-10
	> Z-3

OPTIONAL

	> W-2
	- AF-4R
	> WTR-20
	> Z-3
	> W-1
	- AF-5XR
	> AF-5X-HB
	> SC-2
	> WTR-20

BUBBLE

	> W-1
	> W-101-HB
	> B-200-HB
	> BCT-1
	> BCR-1

FIRE TRAINING

	> FLIGHTCASE
	> FT-20X-B
	> FT-20X-BCL
	> FLM-05P
	> Z-3

	> WTR-20
	> FT-20XS
	> W-3
	> W-2
	> Z-3

SCENT

	> SCN-600-HB
--	--------------

LIQUID SUPPLY

	> XLR 4-PIN
	> 10 METER 6 X 4MM TUBE
	> FTA-64
	> FLUID FILTER
	> Z-8
	> SC-2
	> XLR 3-PIN
	> 12 METER 6 X 4MM TUBE
	> 10 METER 4 X 2.5MM TUBE
	> ADAPTOR
	- 4 TO 4 MM ADAPTOR
	- 6 TO 4 MM ADAPTOR
	> FLUID FILTER

MODEL	RATED POWER	WARM UP TIME	OUTPUT	FLUID TANK CAPACITY	HANGING BRACKET	REMOTE CONTROL	DMX	W-DMX	TIMER REMOTE	WIRELESS REMOTE	CONTINUOUS OUTPUT
AF-3/AF-3X AF-3S	127W	N/A	N/A	N/A	YES	▲Z-3	YES	N/A	N/A	▲WTR-10	YES
AF-4 AF-4R	100W	N/A	N/A	N/A	YES	▲Z-3	YES	N/A	N/A	▲WTR-20 W-2(AF-4R)	YES
AF-5X AF-5XR	1600W	N/A	N/A	N/A	▲ AF-5X-HB	N/A	YES	N/A	N/A	W-1(AF-5XR)	YES
AF-6	250W	N/A	N/A	N/A	YES	▲SC-2	YES	N/A	N/A	▲WTR-20	YES
B-100	120V 30W 240V 32W	N/A	N/A	0.7 L	YES	N/A	N/A	N/A	N/A	N/A	YES
B-200	120W	N/A	N/A	2 L	YES	N/A	YES	N/A	▲BCT-1	▲BCR-1	YES
CH-1	120V 700W 240V 1.250W	8 MIN (APPROX.)	N/A	2.5 L	N/A	N/A	YES	▲TIMO-W-DMX-PCBR	N/A	N/A	YES
DNG-100	120V 750W 240V 600W	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DNG-250	1600W	6 MIN (APPROX.)	120M ² /MIN	10 L	N/A	N/A	YES	N/A	N/A	N/A	YES
F-1	800W	4.5 MIN (APPROX.)	N/A	2.4 L	N/A	N/A	YES	▲TIMO-W-DMX PCBR ▲TIMO-WTR-40	N/A	▲WTR-10 ▲TIMO-WTR-40	YES
F-6	1.450W	1 MIN (APPROX.)	N/A	5 L	N/A	N/A	YES	▲ES-W-DMX	N/A	▲WTR-110	YES
F-7X	100V 1.400W 120V 1.600W 240V 1.900W	7 MIN (APPROX.)	N/A	5 L*2PCS	N/A	N/A	YES	▲ES-W-DMX	N/A	▲WTR-110	YES
F-12	100V 550W 120V 750W 240V 1.300W	8 MIN (APPROX.)	N/A	5 L	N/A	N/A	YES	▲ES-W-DMX	N/A	▲WTR-110	YES
FT-20X	600W	1 SEC (APPROX.)	N/A	0.4 L	N/A	▲Z-3	YES	N/A	N/A	▲WTR-20	YES
FT-70	1.000W	7 MIN (APPROX.)	N/A	1.7 L	N/A	N/A	N/A	N/A	N/A	W-3	YES
FT-100	120V 1.500W 240V 1.450W	8.5 MIN (APPROX.)	N/A	6 L	N/A	▲Z-3	YES	N/A	N/A	W-2	YES
FT-200	1.600W	7.5 MIN (APPROX.)	8 METER HEIGHT	2.4 L	N/A	▲Z-3	YES	N/A	N/A	W-2	YES
HZ-100	390W	N/A	N/A	2.5 L	N/A	N/A	N/A	N/A	▲HC-1	▲HCR-1	YES
HZ-350	390W	N/A	N/A	2.5 L	N/A	N/A	YES	N/A	▲HC-1	W-1	YES
HZ-400	470W	N/A	N/A	2.5 L	N/A	N/A	YES	N/A	HC-1	▲HCR-1	YES
HZ-500	120V 400W 240V 480W	N/A	N/A	2.5 L	N/A	N/A	YES	N/A	N/A	N/A	YES
HZ-1000	1.150W	N/A	N/A	6.4 L	N/A	N/A	YES	▲TIMO-W-DMX-PCBR	N/A	N/A	YES
ICE-101	1.130W	4.5 MIN (APPROX.)	43M ² /MIN	2.5 L	N/A	N/A	YES	N/A	Z-8	N/A	NO
IP-1600	1.500W	12 MIN (APPROX.)	N/A	N/A	YES	N/A	YES	N/A	N/A	W-2	YES
IP-3000	2.500W	12 MIN (APPROX.)	N/A	N/A	YES	N/A	YES	N/A	N/A	W-2	YES
LCU-1S	40W	N/A	N/A	N/A	N/A	N/A	YES	N/A	N/A	N/A	N/A

▲ OPTIONAL

MODEL	RATED POWER	WARM UP TIME	OUTPUT	FLUID TANK CAPACITY	HANGING BRACKET	REMOTE CONTROL	DMX	W-DMX	TIMER REMOTE	WIRELESS REMOTE	CONTINUOUS OUTPUT
LCU-2S	55W	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
M-5	1.500W	8 MIN (APPROX.)	N/A	10 L	▲M-5-HB	M-20	YES	N/A	M-20	▲M-30PRO	YES
M-7X	1.516W	7 MIN (APPROX.)	10 METERS HEIGHT	2.4 L	N/A	N/A	YES	▲TIMO-WTR-90	N/A	W-2	NO
M-8	1.700W	9.5 MIN (APPROX.)	N/A	10 L	▲M-5-HB	M-21	YES	N/A	M-21	▲M-31	NO
M-9	1.820W	14 MIN (APPROX.)	10 METERS HIGHT	6 L	▲M-9-HB x 2	N/A	YES	▲TIMO-WTR-90	N/A	W-2	NO
M-10	3.000W	9.5 MIN (APPROX.)	N/A	10 L	N/A	M-20	YES	N/A	M-20	▲M-30PRO	YES
M-12	2.000W	13 MIN (APPROX.)	N/A	10 L	▲M-12-HB	N/A	YES	▲ES-W-DMX	N/A	▲WTR-110	YES
MB-1	75W	1 SEC	N/A	110 ML	N/A	N/A	N/A	N/A	▲MCT-2	▲MCR-1F	YES
MB-20X	600W	1 SEC	N/A	0.4 L	N/A	▲Z-3	YES	N/A	N/A	▲WTR-20	YES
S-100X	880W	N/A	N/A	5 L	YES	SC-2	YES	N/A	N/A	N/A	YES
S-200X	880W	N/A	N/A	5 L	YES	SC-2	YES	N/A	N/A	N/A	YES
SW-250	900W	N/A	N/A	5 L	YES	▲SC-2	YES	N/A	N/A	W-1	YES
SW-300	880W	N/A	N/A	5 L	YES	▲SC-3	YES	N/A	N/A	W-1	YES
S-500	900W	N/A	N/A	20 L	N/A	▲SC-3	YES	▲TIMO-W-DMX PCBR ▲TIMO-WTR-70	N/A	▲WTR-20 ▲TIMO-WTR-70	YES
S-600	1.200W	N/A	N/A	N/A	YES	▲SC-4	YES	▲TIMO-WTR-90	N/A	W-2	YES
SCN-600	7W	N/A	N/A	150 ML	▲SCN-600-HB	N/A	YES	N/A	N/A	N/A	YES
W-101	32 W	N/A	N/A	0.7 L	YES	N/A	N/A	N/A	N/A	W-1	YES
W-508	800W	2 MIN (APPROX.)	N/A	0.8 L	N/A	N/A	N/A	N/A	N/A	W-1	YES
Z-350	120V 700W 240V 750W	4.5 MIN (APPROX.)	N/A	1.3 L	N/A	▲Z-3	YES	N/A	N/A	N/A	YES
Z-390	120V 1.000W 240V 1.450W	1.5 MIN (APPROX.)	N/A	4 L	YES	▲Z-3	YES	N/A	N/A	▲WTR-20	YES
Z-1520	1.516 W	5 MIN (APPROX.)	6 METERS HEIGHT	2.4 L	N/A	N/A	YES	N/A	N/A	W-2	NO
Z-800III	800W	2 MIN (APPROX.)	N/A	0.8 L	N/A	Z-10	N/A	N/A	▲Z-40	▲Z-50	YES
Z-1000III	1.000W	6 MIN (APPROX.)	N/A	1.7 L	YES	Z-10	YES	N/A	▲Z-40	▲Z-50	NO
Z-1200III	1.200W	11 MIN (APPROX.)	N/A	2.5 L	YES	▲Z-3	YES	N/A	▲Z-40	▲Z-50	YES
Z-1500III	1.500W	9 MIN (APPROX.)	N/A	6 L	N/A	N/A	YES	N/A	N/A	▲WTR-20	YES
Z-3000III	2.500W	10 MIN (APPROX.)	N/A	6 L	N/A	N/A	YES	N/A	N/A	▲WTR-20	YES

▲ OPTIONAL